

APPLICATION FOR UNITED STATES LETTERS PATENT

FOR

INFORMATION ACCESS IN USER MODEL-BASED INTERACTIVE
TELEVISION

Inventor(s): **Anthony F. Istvan**
James C. Broadus

Prepared by:

BLAKELY SOKOLOFF TAYLOR & ZAFMAN LLP
12400 Wilshire Boulevard, 7th Floor
Los Angeles, California 90025
(425) 827-8600

"Express Mail" Label Number EL429890145US

Date of Deposit June 28, 2001

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Box Patent Application, Washington, D.C. 20231.

Jenny E. Miller
Jenny E. Miller

6-28-01
Date

INFORMATION ACCESS IN USER MODEL-BASED INTERACTIVE TELEVISION

5 CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of U.S. Provisional Patent Application No. 60/267,215 entitled "User Model for Interactive Television System," filed February 7, 2001 and is incorporated herein by reference.

10

TECHNICAL FIELD

This disclosure relates generally to interactive television systems, and in particular but not exclusively, relates to systems for controlling access to
15 interactive television systems.

BACKGROUND

/

20 Televisions and Internet technologies are beginning to converge. For example, the Internet is gaining television like qualities, such as the capability to play videos and music, and to broadcast live video feeds, and televisions are becoming more interactive like the Internet. In particular, access to the World Wide Web via Internet-enabled television systems is progressing and becoming more popular. Such television systems allow users to access both Web content information and
25 television content information from a single system. The content information may contain content that is offensive or inappropriate for viewing by certain viewers, e.g. children.

Conventional systems typically use a set top box (STB) to provide access to the interactive television system. These systems tend to treat each STB as an independent unit. These systems are disadvantageous in various aspects. First, they typically allow only primitive configuration functions. Second, they typically do not provide convenient support across multiple access devices. Third, they typically do not provide convenient support across multiple applications and services.

BRIEF DESCRIPTION OF THE DRAWINGS

Non-limiting and non-exhaustive embodiments of the present invention are described with reference to the following figures, wherein like reference numerals refer to like parts throughout the various views unless otherwise specified.

Figure 1 is a simplified diagram illustrating an interactive television system, according to one embodiment of the present invention.

Figure 2 is a step diagram illustrating a client system, according to one embodiment of the present invention.

Figure 3 is a step diagram illustrating an exemplary device, according to one embodiment of the present invention.

Figure 4 is a diagram illustrating an exemplary control device, according to one embodiment of the present invention.

Figure 5 is a logical object diagram illustrating a single household user model, according to one embodiment of the present invention.

Figure 6 is a logical object diagram illustrating a multi-household user model, according to one embodiment of the present invention.

Figure 7 is a diagram illustrating components of a logical object, according to one embodiment of the present invention.

Figure 8 is a diagram illustrating components of a user object, according to one embodiment of the present invention.

Figure 9 is a flow diagram illustrating the operational flow in using a user model as depicted in Figure 5, according to one embodiment of the present invention.

Figure 10 is a flow diagram illustrating the addition a new user object to a household, according to one embodiment of the present invention.

Figure 10A is a flow diagram illustrating the reception of user information for a first user object, according to one embodiment of the present invention.

Figure 11 is a diagram illustrating a revision history, according to one embodiment of the present invention.

Figure 12 is a flow diagram illustrating one embodiment of providing update information to access devices in a household, according to the present invention.

Figure 13 is a flow diagram illustrating one embodiment of receiving of update information for a user object, according to the present invention.

Figure 14 is a flow diagram illustrating one embodiment of determining an update for a particular access device, according to the present invention.

Figure 15 is a flow diagram illustrating one embodiment of adding a new access device to a household, according to the present invention.

Figure 16 is a flow diagram illustrating one embodiment of adding a user object to a household, according to the present invention.

Figure 17 is a flow diagram illustrating one embodiment of revising a user object, according to the present invention.

Figure 18 is a flow diagram illustrating one embodiment of using a single password to access multiple password protected services.

DETAILED DESCRIPTION OF THE ILLUSTRATED EMBODIMENTS

Embodiments of a system and method for accessing an interactive television system are described herein. In the following description, numerous specific details are provided, such as implementations of client systems and devices, to provide a thorough understanding of embodiments of the invention. One skilled in the relevant art will recognize, however, that the invention can be practiced without one or more of the specific details, or with other methods, components, materials, etc. In other instances, well-known structures, materials, or operations are not shown or described in detail to avoid obscuring aspects of the invention.

Reference throughout this specification to “one embodiment” or “an embodiment” means that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment of the present invention. Thus, the appearances of the phrases “in one embodiment” or “in an embodiment” in various places throughout this specification are not necessarily all referring to the same embodiment. Furthermore, the particular features, structures, or characteristics may be combined in any suitable manner in one or more embodiments.

In accordance with aspects of the present invention, a user model for interactive television systems is provided. In one aspect, the user model organizes access devices (e.g., STBs) into household objects (or simply “households”), with each access device in a household being logical extensions of each other. In particular, each access device has a corresponding access device “object” associated with a household.

In addition, each household can have multiple user objects, with each user object having its own independent configuration of attributes and data. This

aspect of the present invention allows a user to create or reconfigure a user object by logging on to an authorized user object at any one of the access devices of the household. The other access devices (if any) in the household automatically receive the user object information of a new or reconfigured user object without any further action by the user. Thus, this aspect advantageously allows a single operation to configure and/or reconfigure all of the access devices in a household with the user object information of a new or revised user object. In a related aspect of the present invention, when a user adds a new access device to the household, the new access device automatically receives the user object information of user objects already existing in the household, without any further action by the user. In one embodiment, this automatic exchange of user object information is coordinated by a server that stores the configuration information of each household and its associated user objects. This server, for example, can be operated by a multiple service operator (MSO) or service provider. Alternatively, the server may be at a broadcast center for a satellite broadcast system.

In another aspect of the present invention, the information of a user object is updated using a revision information file. An access device sends updated user object information to a server when a user changes the user object information of a user object via that access device. In one embodiment, the server receives the updated user object information and stores the updated information in a file corresponding to the user object. In addition, the server creates an update entry for the received update information, which is stored in a list. The update entry includes a ticket number, and a bit vector with the bit corresponding to the updated information being set. The ticket number is incremented for each new update entry.

To update the user object information of user object in a particular access device, the server receives the ticket number of the access device's current

configuration for that user object. The server then determines an update vector for that access device as a function of the access device's bit vector current ticket number and more recent bit vectors from other access devices. In one embodiment, the server then provides the update vector to that access device. That
5 access device can then request the updated user object information corresponding to each set bit in the update vector. This operation is performed for all of the access devices in the household on an ongoing basis.

In yet another aspect of the invention, the user model supports associating multiple usernames and passwords to a user object. This aspect allows
10 the user object to contain the user names and passwords to access various applications and services that may require separate passwords. For example, the interactive television system may provide, in addition to the basic interactive service, pay per view (PPV), parental control, video on demand (VOD) and electronic wallet applications or services. This aspect advantageously allows a user to access all of
15 these applications and services using a single username and password. In a further refinement, any activity that initiates a billing event can cause a password challenge for verification before proceeding with the activity.

The present invention provides techniques for controlling access to an interactive television system. Figure 1 depicts a simplified diagram of a system 100
20 for distributing Internet content and television content in which an embodiment of the present invention may be embodied. In accordance with an embodiment of the present invention, system 100 is integrated with a cable TV distribution system. Such cable television distribution systems may include cable headends (H/Es), which are well known in the art.

25 As shown in Figure 1, system 100 includes a communication network 102, several content sources 104₁-104_N, several broadcast

centers 106₁-106_M and several client systems (CSs) 108₁₁-108_{MJ}. In addition, system 100 also includes a server of the interactive television service provider, which can reside in one or more of broadcast centers 106₁-106_M. In accordance with the present invention, CSs 108₁₁-108_{MJ} (more particularly, access devices that are part of the CSs) are part of households 121₁₁-121_{YZ}. As will be described in further detail below, households allow for advantages in reconfiguring certain aspects of the CSs.

Communication network 102 provides a mechanism for distributing multimedia content from content sources 104₁-104_N to broadcast centers 106₁-106_M.

Communication network 102 may itself be comprised of many networks, interconnected computer systems and communication links. While in one embodiment, communication network 102 is the Internet, in other embodiments, communication network 102 may be any suitable computer network. For purposes of describing the present invention, it will be assumed that communication network 102 is the Internet. Communications over Internet 102 are accomplished using standard protocols such as TCP/IP (transmission control protocol/internet protocol) and other protocols. System 100 depicted in Figure 1 is merely illustrative of an embodiment incorporating the present invention and does not limit the scope of the invention as recited in the claims. One of ordinary skill in the art would recognize other variations, modifications, and alternatives.

As shown in Figure 1, content sources 104₁-104_N may be connected to Internet 102. Additionally, content sources 104₁-104_N may be connected to several data feeds, servers, and information sources that in turn provide content information to content sources 104₁-104_N. For example, content source 104₁ may be connected to receive content information from data feeds 112, advertisement servers 114, image sources 116, streaming multimedia sources 118, including streaming audio

and streaming video sources, and other like sources of content information. For example, news or stock quote feeds 112 may be fed into content source 104₁, servers 114 may provide advertisements for insertion into multimedia content delivered by content source 104₁, and sources 116 and 118 may provide images, streaming video, and other content to content source 104₁. Various other feeds, servers and sources may also be connected to content source 104₁. Examples of content sources 104₁ include web site portals such as Go2Net.com, or news web sites such as CNN.com, and the like. Similarly, (although not shown in Figure 1 to promote clarity) content sources 104₂-104_N may also receive content information from data feeds 112, advertisement servers 114, image sources 116, streaming multimedia sources 118.

Content sources 104₁-104_N may also be connected directly to broadcast centers 106₁-106_M via communication links or communication networks 120. Communication links 120 may include may be hardwire links, optical links, satellite or other wireless communication links, wave propagation links, or any other mechanisms for communication of multimedia content information.

Broadcast centers 106₁-106_M may be connected to Internet 102, and to content sources 104₁-104_N via communication links 120. Each broadcast center 106₁-106_M may also be connected to several CSs. For example, broadcast center 106₁ may be connected to CSs 108₁₁-108_{1L}, broadcast center 106₂ may be connected to CSs 108₂₁-108_{2K}, and so on, to broadcast center 106_M, which may be connected to CSs 108_{M1}-108_{MJ}. Each broadcast center is configured to receive content information from its corresponding content source and/or from Internet 102, and to forward the content information to its corresponding CSs. The content information may include Web content information, television content information and other multimedia content information. In a specific embodiment of the present

invention, as shown in Figure 1, broadcast centers 106₁-106_M comprise cable headends (H/Es).

A satellite TV delivery system may comprise a direct broadcast satellite (DBS) system. A DBS system may comprise a small 18-inch satellite dish (which is an antenna for receiving a satellite broadcast signal); a digital integrated receiver/decoder (IRD), which separates each channel, and decompresses and translates the digital signal so a television can show it; and a remote control. Programming for a DBS system may be distributed, for example, by multiple high-power satellites in geosynchronous orbit, each with multiple transponders. Compression (e.g., MPEG) is used to increase the amount of programming that can be transmitted in the available bandwidth.

A digital broadcast center may be used to gather programming content, ensure its digital quality, and transmit the signal up to the satellites. Programming may come to the broadcast center from content providers (TBS, HBO CNN, ESPN, etc.) via satellite, fiber optic cable and/or special digital tape. Satellite-delivered programming is typically immediately digitized, encrypted and uplinked to the orbiting satellites. The satellites retransmit the signal back down to every earth-station -- or, in other words, every compatible DBS system receiver dish at customers' homes and businesses. Some programs may be recorded on digital videotape in the broadcast center to be broadcast later. Before any recorded programs are viewed by customers, technicians may use post-production equipment to view and analyze each tape to ensure audio and video quality. Tapes may then be loaded into a robotic tape handling systems, and playback may be triggered by a computerized signal sent from a broadcast automation system. Back-up videotape playback equipment may ensure uninterrupted transmission at all times.

As previously mentioned, in accordance with the present invention, the CSs are organized into households. For example, in this embodiment, a household 121₁₁ includes CSs 108₁₁ and 108₁₂. A household can include a single CS as shown for example, by a household 121_{1W} that includes only CS 108_{1L}.
5 Further, as shown in Figure 1, a broadcast center can support one or more households.

Each CS can receive multimedia content, including Web content and television content, from its corresponding broadcast center. Each CS can then output received multimedia content to a user of the household containing the CS.
10 For example, in the embodiment of Figure 1, CS 108₁₁ receives multimedia content from broadcast center 106₁ and outputs the multimedia content to a user of household 121₁₁. In one embodiment, each CS includes an access device that allows a user to receive authorized multimedia content and to communicate with the server of the interactive television service provider.

15 In addition, according to the present invention, each household can have multiple user objects, with each user object having its own independent configuration of attributes and data. For example, a user object may have an administrator attribute, when enabled, allows the user object to change the configuration of other user objects. Attributes and data are described below in more
20 detail in conjunction with Figures 7 and 8.

In general, a user accesses the interactive television system by logging on to a user object. A user can create or reconfigure a user object via any one of the CSs in the household by logging on to an authorized user object (e.g., a user object that has its administrator attribute enabled). The server of the
25 interactive television service provider receives information related to the new or reconfigured user object and provides update information to the other CSs (if any) in

the household. In this way, other CSs in the household are automatically reconfigured with the new user object information without any further action by the user. Thus, a user can configure all of the CSs in a household with a new or revised user object in a single operation. As will be described below, one embodiment of a
5 CS includes an "access device" that can store information (including information related to user objects associated with the household). Thus, households are also described herein as having "access devices" rather than CSs (which can include components in addition to an access device).

In another aspect of the present invention, when a user has a new CS
10 added to the household, information associated with the new CS is received by the server of the interactive television service provider. This server can then provide the most recent user object information to the new CS. In one embodiment, a user must be logged onto a user object with its administrator attribute enabled to add a new CS to the household. In this way, the new CS automatically receives the user
15 objects associated with the household without any further action by the user.

In yet another aspect of the invention, user objects can also contain the separate usernames and passwords that may be needed to access various applications and services that the interactive television system provides. For example, the interactive television system may provide, in addition to the basic
20 interactive service, pay per view (PPV), parental control, video on demand (VOD) and electronic wallet applications or services. These applications and services, in addition to having different usernames and passwords, may also be linked to specific access devices. This aspect advantageously allows a user to access all of these applications and services using a single username and password. In contrast,
25 some conventional systems require that a user remember several different usernames and passwords for the various applications and services and may even

require different usernames and passwords to access the same service from different access devices. In a further refinement, any activity that initiates a billing event can cause a password challenge for verification before proceeding with the activity.

5 Embodiments of processes using the user model are described below in conjunction with Figures 5-17. However, embodiments of hardware used to implementing the processes are described next.

10 Figure 2 depicts a simplified step diagram of a CS 108 according to an embodiment of the present invention. CS 108 can be used to implement any or all of CSs 108₁₁-108_{MJ} (Figure 1). This embodiment of CS 108 includes an access device 130 connected to an output device 132 via communication link 142, and a control device 138 connected to access device 130 via a communication link 140. Access device 130 can be a STB, a personal computer, Web Pad (e.g., a personal computer in tablet form that uses a touch screen rather than a keyboard), or a
15 personal digital assistant (PDA), a cell phone, or a hybrid device combining some of the features and functionalities of the preceding devices, suitable for interacting with the Internet, cable system operator and/or other media service operators.

20 Output device 132 is configured to output multimedia content information to the user of CS 108. In some embodiments, output device 132 may be implemented as a television or other display device, or can be built in as part of access device 130 (e.g., personal computer, PDA or other like device). In a preferred embodiment of the present invention, access device 130 and output device 132 is part of a broadband Internet-enabled television system.

25 Output device 132 may include an audio output device 134 for outputting audio information to the user, and a display device 136 for outputting video, image, and text information to a user. Display device 136 may be a cathode

ray tube (CRT), a flat-panel device such as a liquid crystal display (LCD), a projection device, or any other device suitable for outputting visual information, including streaming video, images, and text, to the user. Audio output device 134 may be a speaker, or any other device suitable for outputting audio information embedded in the Web content and television content received from a broadcast center (see Figure1) to the user. Although, Figure 2 depicts an output device in which display device 136 and audio output device 134 are integrated into one output device 132, in alternate embodiments of the present invention the display device and the audio output device may be embodied in separate devices.

Control device 138 may be used by the user to control the functionality of CS 108. Control device 138 communicates with access device 130 via communication link 140 that is generally an infrared (IR) communication link. However, in alternate embodiments of the present invention, communication link 140 may also be a hardwire link, an optical link, or any other means for communicating information from control device 138 to access device 130. Control device 138 may be embodied as a television remote control device, a keyboard, a mouse, or any other device which allows a user to input information to CS 108.

According to an embodiment of the present invention, access device 130 is implemented as a STB that includes hardware and software to receive multimedia content information, including Web content and television content, from broadcast centers 106₁-106_M (Figure 1). Access device 130 also contains hardware and software to output the multimedia content to the user via output device 132. Access device 130 also performs functions allowing the user to control the manner in which the multimedia content is downloaded to CS 108 and presented to the user. Access device 130 includes components and modules that regulate a user's access to Web and television content output by access device 130. Access device 130 is

connected to output device 132 via communication link 142. Communication link 142 may include a video channel for communicating video information from access device 130 to output device 132 and an audio channel for communicating audio information from access device 130 to output device 132.

5 Figure 3 is a simplified step diagram of an exemplary access device 130 according to an embodiment of the present invention. Access device 130 typically includes at least one processor 162 that communicates with a number of peripheral devices via a bus subsystem 160. These peripheral devices may include a storage subsystem 164, comprising a memory subsystem 166 and a
10 file storage subsystem 172, a video subsystem 178, an audio subsystem 176, a broadcast center interface subsystem 174, and a control device interface subsystem 180.

 Distribution interface subsystem 174 provides an interface for receiving multimedia content information from broadcast center 106. The
15 multimedia content is then processed and forwarded to display device 136 and/or to audio output device 134 for output to the user. Control device interface subsystem 180 detects signals received from control device 138 and provides instructions/information encapsulated in the signals to processor 162 for further processing.

20 Audio subsystem 176 is responsible for processing audio content received from broadcast center 106, and transmitting the processed audio signals to audio output device 134 for output to the user. Likewise, video subsystem 178 is responsible for processing video content received from broadcast center 106, and transmitting the processed video signals to display device 136 for output to the user.

25 Storage subsystem 164 stores the basic programming modules and data constructs that provide the functionality of the various systems embodying the

present invention. For example, databases and modules implementing the functionality to regulate access to Web and television content according to the teachings of the present invention may be stored in storage subsystem 164. Processor 162 generally executes these software modules. Storage subsystem 164
5 may comprise memory subsystem 166 and file storage subsystem 172.

Memory subsystem 166 typically includes a number of memories including a main random access memory (RAM) 170 for storage of instructions and data during program execution and a read only memory (ROM) 168 in which fixed instructions are stored. File storage subsystem 172 provides persistent (non-volatile) storage for program and data files, and may include a hard disk drive, a
10 floppy disk drive along with associated removable media, a Compact Digital Read Only Memory (CD-ROM) drive, an optical drive, or removable media cartridges. The databases and modules implementing the functionality of the present invention may also be stored by file storage subsystem 172.

Bus subsystem 160 provides a mechanism for letting the various components and subsystems of access device 130 communicate with each other as intended. Although bus subsystem 160 is shown schematically as a single bus, alternate embodiments of the bus subsystem may utilize multiple buses. Further, in alternate embodiments of the present invention, the various components of access
15 device 130 may be directly connected to processor 162.

Due to the evolving nature of processing units 130, the description of access device 130 depicted in Figure 3 is intended only as a specific example for purposes of illustrating the preferred embodiment of the present invention. Many other configurations of access device 130 are possible having more or less
25 components than the access device 130 depicted in Figure 3. In light of this

disclosure, those skilled in the art will be able to implement different embodiments of access device 130 without undue experimentation.

As previously mentioned, according to an embodiment of the present invention, access to multimedia content is regulated by defining or configuring one or more user objects of CSs 108₁₁-108_{MJ} (Figure 1). Each user object specifies a level of access to the Web or television content information. Each user object is generally characterized by attributes such as, for example, a user identification code that is used to identify the user object, and a set of privileges associated with the user object. Using CS 108 (Figure 2) as an example, a user of CS 108 may log onto a particular user object, which may require the user to enter a password. The privileges associated with that particular user object define: (1) the Web or television content that the user can access and (2) the manner in which the user interacts with system 100 (Figure 1). In a specific embodiment of the present invention, information related to the various user objects is stored in access device 130 of CS 108 and in the server of the interactive television service provider.

Figure 4 depicts an exemplary control device 150 according to an embodiment of the present invention. Control device 150 may be used to control the functionality of CS 108 (Figure 2). As shown, control device 150 has the general appearance of a common, hand-held remote comprising several buttons to control the functions of CS 108 (Figure 2).

Figure 5 illustrates logical objects of a single household system 200, according to one embodiment of the present invention. This embodiment of the system 200 includes four types of logical objects; *i.e.*, an account 201, a household 202, user objects UO₁-UO_f and access device objects AD₁-AD_g. System 200 illustrates the relationship between the logical objects of a single household model. User objects UO₁-UO_f and access device objects AD₁-AD_g are

associated with household 202, which in turn is associated with account 201. Account 201 represents an account maintained by the interactive television service provider for record keeping and billing purposes (e.g., a multi-service operator (MSO) account). User objects UO_1-UO_f and access device objects AD_1-AD_g are, in effect, contained in household 202 so that, for example, a change in one of user objects UO_1-UO_f will apply to all of the access device objects AD_1-AD_g . In addition, in one embodiment, a single user object may be simultaneously logged on in several access devices.

Figure 6 illustrates logical objects of a multi-household user system 220, according to one embodiment of the present invention. System 220 is similar to system 200 (Figure 5) except that instead of a single household 202 (Figure 5), system 220 includes an account 221 associated with multiple households. In the exemplary system shown in Figure 6, system 220 includes households HH_1-HH_q , with each of these households having user objects and access device objects. In this embodiment, household HH_1 is associated with user objects $UO_{11}-UO_{1f}$ and access device objects $AD_{11}-AD_{1g}$; household HH_2 is associated with user objects $UO_{21}-UO_{2h}$ and access device objects $AD_{21}-AD_{2i}$; and so on to household HH_q , which is associated with user objects $UO_{q1}-UO_{qr}$ and access device objects $AD_{q1}-AD_{qt}$.

Figure 7 illustrates elements associated with a general logical object 230, according to one embodiment of the present invention. As previously described, accounts, households, user objects, and access devices are all represented as logical objects in the user model. Also described above, in accordance with the present invention, a logical object is associated with attributes and data. In Figure 7, these are indicated as attributes 231 and data 232. In this embodiment, attributes 231 are related to predefined characteristics of the logical

object. For example, a user object's attributes may include an administrator attribute (which if enabled allows the user object to have access to defined administrative privileges), an email attribute (which if enabled allows the user object to send and receive email), among other characteristics. In this embodiment, data is information that is stored on behave of the logical object. For example, a user object's data may include a user name, a channel list (a list of channels that the user object has permission to view), among other types of information. Tables 1-4 in Appendix A summarize attributes and data that can be used for user object, household, access device and account logical objects, respectively.

Figure 8 illustrates attributes and data associated with an exemplary user object 240, according to one embodiment of the present invention. In this embodiment, in addition to the administrator and email attributes previously described, attributes 231 associated with user object 240 can include a "pay per view" (PPV) attribute, which allows the user object to view PPV programs when enabled. In addition, attributes 231 can include a "deleted" attribute (which when set indicates that the user object has been deleted from the household), and a "password" attribute (which when set allows the user object to log on into the user object without having to enter a password). In other embodiments, user object 240 may have other attributes such as, for example, those listed in Table 1 of Appendix A. Information related to attributes 231 and data 232 can be stored in the server of the interactive television system and in the access device(s) of a household.

In this embodiment, data 232 associated with user object 240 can include a channel list 244, a list of favorite television channels 245, a list of favorite web sites 246, and revision information 247. Revision information 247, in this embodiment, includes a ticket number 248. Ticket number 248 is used in updating

the user object's information in all of the access devices in the same household as user object 240. Ticket number 248 and the updating process are described in more detail below. In an alternative embodiment, revision information 247 may be part of attributes 231 because revision information 247 generally does not include information directly provided by a user (rather in one embodiment the server generates the revision information from data provided by the user). Data 232 may also include email messages 249 when the email feature is used. In other embodiments, data 232 can include other types of data such as, for example, those listed in Table 1 of Appendix A. As previously mentioned, some or all of this information can be stored in the server and in the access device(s) of a household. For example, an access device can store information such as channel list 244, television favorites 245, web favorites 246 and revision information 247.

Figure 9 illustrates an operational flow in using a user model according to one embodiment of the present invention. In a step 260, the operational flow begins with creating an account. For example, in one embodiment, a customer can open the account with an interactive television service provider (e.g., a MSO). The interactive television service provider operates a server used to control access to services and multimedia content provided by the interactive television service provider. As previously described, this server can reside in one or more of broadcast centers 106₁-106_M (Figure 1). The interactive television service provider instantiates the new account so that the server can access information associated with the account.

In a step 262, a household for the account is created. Continuing the example described above in conjunction with step 260, the interactive television service provider instantiates a household for the customer, which is associated with the account created in step 260. In other embodiments, the interactive television

service provider can create more than one household for the account. The server can access information associated with the household.

In a step 264, an access device object is created and associated with the household created in step 262. In one embodiment, when a user connects the physical access device to a broadcast center (e.g., a H/E), the server detects the physical access device and instantiates a corresponding access device object. The server associates the access device object to the household. One embodiment of a process of entering information for a new access device object is described below in conjunction with Figure 15.

Although steps 260, 262 and 264 are described sequentially, in light of the present disclosure, those skilled in the art can implement other embodiments in which these steps are performed in different orders. For example, in one embodiment, the household may be created before the account is created. In another embodiment, installing the first access device can cause steps 260 and 262 to be performed.

In a step 266, a user object is created and associated with the household created in step 262. In previously mentioned, a user can access the interactive television system via an installed access device to create a user object. In addition, in one embodiment of step 266, a first user object is automatically created or instantiated when the first access device is installed. This first user object is automatically given permission to access all of the features and privileges supported by the interactive television system. Thus, in one embodiment, the first user object is instantiated as an administrator, which allows this user object to create and modify other user objects. An authorized user can use this first user object to add other user objects and access device objects as described below.

In a step 268, the household and/or account is validated. This operation can be used to verify that the interactive television service provider has not terminated service for that particular household or account. In one embodiment, the server verifies that the household or account is authorized to access the interactive television system. If the account or household is not valid, the operation terminates; otherwise, the operational flow proceeds to a step 270.

In step 270, the interactive television system is monitored for updates related to user objects and access device objects. For example, in one embodiment, the server of the interactive television service provider can be configured to detect, *inter alia*, installation of a new access device, addition of a new user object to the household, and revision of information for an existing user object or access device object. In one embodiment, a user can upload this update information via one of the access devices that are installed on the interactive television system. If the server does not detect any such update, the operational flow loops back to step 268. Conversely, if the server does detect an update, the operational flow proceeds to a step 272.

In step 272, the update information is received and stored for the household by the interactive television system. In one embodiment, the server stores this received update information. In this embodiment, the server maintains a record of information for the account logical object, and the associated household, user and access device logical objects.

In a step 274, the update information is then distributed to the access devices associated with the household. In one embodiment, the server sends the update information received via an access device to all of the other access devices of the household. One embodiment of this operation is described in more detail

below, in conjunction with Figure 12. The operational flow then loops back to step 268.

Although steps 268, 270, 272, and 274 are described sequentially, in light of the present disclosure, those skilled in the art can implement other
5 embodiments in which the steps are performed in a different order, or with some steps performed concurrently.

A situation may arise when a user attempts to update information for a logical object while another user is already updating that particular logical object. In one embodiment, the most recent update information is used while the earlier
10 update information is disregarded (*i.e.*, the race condition is resolved using last-in semantics). In another embodiment, the first user to begin the updating operation locks out the second user until the first user's update is completed.

Figure 10 illustrates the operational flow of step 266 (Figure 9), according to one embodiment of the present invention. In particular, Figure 10
15 illustrates the addition of a new user object to a household, according to one embodiment of the present invention.

In a step 280, information for a new user object is received. In one embodiment, the server of the interactive television system receives this information from either a user via an access device, or from a customer service representative
20 (CSR) of the interactive television service provider. For example, a user can provide the new user object information to the server via the access device. This user object information can include an identifier (*i.e.*, identifying the particular configuration parameter) and a value for a particular configuration parameter of the new user object. One embodiment of step 280 is described below in conjunction
25 with Figure 10A. In addition, one embodiment of a process by which a user enters a new user object is described below in conjunction with Figure 16.

In a step 282, the received user object information of the new user object is assigned a ticket number. In one embodiment, the server increments the most recent ticket number the server has used and assigns this incremented ticket number to the received user object information. In this way, the server provides an identifier to each received set of user object information.

In a step 284, the ticket number and a bit vector for the received user object information is stored. In one embodiment, the server stores the ticket number and the bit vector in a revision history. The revision history can be of fixed size, with a new entry (*i.e.*, ticket number and corresponding bit vector) replacing the oldest remaining entry if the revision history is full.

In this exemplary embodiment, each bit of the bit vector corresponds to a configuration parameter or setting (hereinafter configuration parameter) of a user object. A bit in the bit vector is set when the corresponding configuration parameter is "updated" (which includes adding a value for a newly created user object).

In a step 286, the ticket number is provided to the particular access device that was used to provide the user object information of the new user. In one embodiment, the server provides the ticket number to the access device. The access device can store the ticket number as a way of keeping track of its configuration. In one embodiment, the access device stores the ticket number in revision information file 247 (Figure 8). In other embodiments, step 286 may be performed before or concurrently with step 284.

Figure 10A illustrates step 280 in which user object information is received, according to one embodiment of the present invention. In one embodiment, a step 287 is performed in which the user object is created. In an embodiment, the server of the interactive television system creates the user object

with default information. For the first user object being created, the default includes setting the administrator attribute. For subsequent user objects, the administrator attribute would not be set. In one embodiment, the server causes the access device to display the default information, which the user or CSR can modify. For example, this information may be presented in a menu. The user or CSR could then select a desired setting and modify it. In another embodiment, the access device may be configured to display the menu when it is first connected to interactive television system 100. In another embodiment, for example, the access device may be configured to prompt the user to enter information for each setting instead of using a menu.

In a step 288, modifications to the default settings are received. In one embodiment, the server receives the modifications from the access device. Alternatively, the modifications can be provided through another mechanism (e.g., from a CSR through a computer terminal). For example, after the user has completed all of the modifications, the access device may prompt the user or CSR for a confirmation and then send the modifications to the server.

In one embodiment, the server receives a series of user object information messages from the access device. Each message has a value for one configuration parameter and a bit vector with the bit corresponding to the configuration parameter being set. The server of the interactive television system stores this user object information.

In an alternative embodiment, the access device would send a message with a bit in the associated bit vector being set to indicate that the user object information corresponds to a new user object. The message would also include the values for all of the configuration parameters in a predefined order.

In a step 289, the user object information is committed to the corresponding household. In one embodiment, after all of the configuration information is received, the server stores the received user object information and associates it with the household of step 262 (Figure 9).

5 Figure 11 illustrates a revision history 292, according to one embodiment of the present invention. In this embodiment, revision history 292 can store N (N being an integer greater than or equal to zero) entries related to a particular household (*i.e.*, each household will have its own revision history). In this exemplary embodiment, revision history 292 includes a ticket number field 294 and
10 a bit vector field 296. Revision history 292 can include other fields (not shown) in other embodiments. In one embodiment, each entry's bit vector can have only one bit set. In the exemplary embodiment shown in Figure 11, revision history 292 is completely filled with N entries. These entries have ticket numbers X through X+N (X being an integer greater than or equal to zero) and corresponding 8-bit bit
15 vectors. For example, the earliest entry in revision history 292 has a ticket number X and a bit vector of "00010000", and latest entry has a ticket number X+N and a bit vector of "00000100". In other embodiments, a bit vector can have more than one bit set. As will be described in more detail below, revision history 292 can be used to determine the updates needed for the access devices in its associated
20 household.

Figure 12 illustrates one embodiment of step 274 (Figure 9), according to one embodiment of the present invention. As previously described, step 274 updates information in access devices in a household.

In a step 301, updated information is received. In one embodiment,
25 the server receives the updated information from an access device of a household. In an alternative embodiment, the updated information is received from another

source (e.g., from a CSR using a computer). One embodiment of step 312 is described in more detail below in conjunction with Figure 13.

In a step 303, updates for each access device in the household are determined. In one embodiment, the server determines these updates using a polling scheme in conjunction with revision history 292 (Figure 11) and the access device's most recent ticket number. One particular implementation of the polling scheme embodiment is described below in conjunction with Figure 14. In other embodiments, when a user instantiates a user object via an access device, the access device may send a message with its most recent ticket number to the server, which then determines the update to send back to that access device using revision history 292. The server may be configured to determine only the updated user object information for the instantiated user object, rather than all the updates for needed by that particular access device. In another embodiment, each access device may be configured to periodically send messages with its most recent ticket number to check for updates.

In a step 305, updated user object information is provided to the access devices in the household. In one embodiment, the server provides the updated user object information determined in step 303 above. For example, when an access device sends its most recent ticket number to the server, the server determines the update as in step 303 and then sends updated user object information to that access device in step 305. In one embodiment, the server would send to the access device an update vector. The update vector would have one or more set bits, each set bit indicating a particular configuration parameter to be updated in that access device. The access device would then request updated information from the server as indicated by the bits that are set in the update vector. In one embodiment, the access device would request the indicated updated user

object information one configuration parameter at a time. This process would then be repeated for all of the other access devices in the household that are coupled to the server.

Figure 13 illustrates an implementation of step 301 (Figure 12),
5 according to one embodiment of the present invention. This process is similar to the process of adding a new user object as described above in conjunction with Figure 10, with a few minor exceptions as described below.

In a step 311, updated user object information for an existing user object is received. In one embodiment, the server of the interactive television system receives this updated user object information from a user via an access
10 device or from a CSR via an access device or computer. One embodiment of a process of entering this updated user object information is described below in conjunction with Figure 17. In accordance with one embodiment of the present invention, the user object information can include a value for the particular configuration parameter being updated and a bit vector with the bit corresponding to
15 that configuration parameter being set. The server of the interactive television system can then store the received updated user object information.

In a step 313, the received updated user object information is assigned a ticket number. In one embodiment, the server increments the most recent ticket
20 number in revision history 292 (Figure 11) and assigns this incremented ticket number to the received user object information.

In a step 315, the ticket number and the bit vector for the received user object information is stored. In this embodiment, the server stores the ticket number and the bit vector in the revision history (Figure 11), replacing the oldest remaining
25 entry if revision history 292 is full.

Figure 14 illustrates an implementation of step 303 (Figure 12), according to one embodiment of the present invention. As previously described, step 303 determines the updated information to provide to a particular access device.

5 In a step 321, a ticket number corresponding to the current configuration of an access device is received. In one embodiment, the server of the interactive television system receives the ticket number from its corresponding access device. For example, an access device could provide the ticket number in response to a query from the server or, alternatively, in response to an instantiation
10 of a user object in that access device (described above in conjunction with Figure 12). The server can keep a record of the ticket number and the access device that provided the ticket number.

In a step 323, an update vector is determined. In one embodiment, the server determines the update vector using the received ticket number and
15 revision history 292 (Figure 11). In this embodiment, for example, the server determines the logical-OR of the bit vectors of all of the entries in revision history 292 associated with ticket numbers that are more recent than the received ticket number. These more recent ticket numbers are associated with updates that occurred after the current configuration of the access device. The resulting update
20 vector will typically have some bits that are set and some that are not, with the set bits indicating configuration parameters that need to be updated. If all of the ticket numbers stored in revision history 292 are more recent than the received ticket number, the server can set all of the bits in the update vector (*i.e.*, indicating that all of the user object information in that access device needs to be updated).

25 In a step 325, the update vector is provided to the access device. In one embodiment, the server provides the update vector to the access device. The

server can provide this update vector to the access device automatically after determining the update vector for that access device. In an alternative embodiment, the server can wait for a request from the access device before providing the update vector to the access device.

5 In a step 327, the server then provides to the access device the user object information corresponding to the set bit or bits of the update vector. For example, as previously described, each time a configuration parameter is updated, the server stores this updated information. Thus, the server should have the most up-to-date configuration of each logical component in the household. In one
10 embodiment, the server can provide the value for each of these configuration parameter(s) in response to a request by the access device. In this embodiment, the access device, having received the update vector, knows which configuration parameters need to be updated. The access device can then request the most recent value of each configuration parameter from the server when convenient for
15 the access device. The access device can request the updates one configuration parameter at a time or in one request. In an alternative embodiment, the server, having determined the update vector, can push the updated values onto the access device.

 In addition, the ticket number associated with each update is provided
20 to the access device. In one embodiment, the server sends this ticket number to the access device along with the corresponding updated user object information. For example, in an embodiment in which the server pushes the updated values to the access device, the server can push them in reverse order (*i.e.*, the most recent update being last). The server can provide the updated value, a bit vector with a bit
25 set to indicate the configuration parameter of the updated value, and the ticket number of the update. The access device can overwrite the ticket number in its

revision information file 247 (Figure 8) with each update received from the server. Alternatively, in an embodiment in which the server provides all of the updates in one message, the server can provide all of the updated values and the ticket number corresponding to the most recent update in the group of updated values.

5 Figure 15 illustrates one embodiment of adding a new access device to a household, according to the present invention. The operational flow starts when a user couples a new access device to the interactive television system (e.g., by connecting the access device to a broadcast center). In this context, a new access device is an access device that does not have an access device object associated with a household. In this exemplary embodiment, the access device is
10 configured to perform the steps of the operational flow.

 In a step 340, the server of the interactive television system is informed that a new access device is being connected to the interactive television system. In one embodiment, the access device is configured to send a message to
15 the server indicating that it has not been associated with a household. In a further refinement, the access device can prompt the user installing the access device to enter the household (e.g., via a household login procedure) and then provide this household information in the message that the access device sends to the server.

 In a step 341, the access device determines whether there are any
20 user objects associated with the household. For example, if the access device is the first access device added to the household, it is possible that the household does not yet have a user object. In one embodiment, in response to the access device's message in step 340, the access device receives a message from the server that indicates whether the access device is the first access device of the
25 household. If the access device is not the first access device of the household, a step 342 is performed in which the access device receives user object information

from the server. For example, the server may send (*i.e.*, push) the most recent user object information for all of the user objects associated with the household (including the most recent ticket number) to the access device. The access device's configuration information can, for example, include a media access control (MAC) address, personal identification numbers (PINs) for various services provided by the interactive television system, and a list of privileges for default operation (*i.e.*, without logging onto a user object). In addition, the access device can provide the access device's configuration information to the server in order to create a new access device object. Alternatively, the access device may request (*i.e.*, pull) the most recent user object information from the server of the interactive television system.

Conversely, if the access device is the first access device of the household, the operational flow proceeds to a step 344, which begins the operation of creating a first user object. In an alternative embodiment, the first user object may have been created by the interactive service provider beforehand when the user subscribed to the service, allowing the user to skip step 344.

In step 344, the access device begins the process to create the first user object. In one embodiment, this first user object is provisioned with default information. The first user object has its administrator attribute automatically enabled. This configuration setting is performed automatically because the first user object to be added to the household generally indicates that a new account is being created. As previously described, when an account is created, a household is automatically created. In addition, when the first access device for the household is activated, the first user object can also be created in step 344. The first user object is created with administrator privileges enabled so that an authorized user can log onto the first user object to create and update other user and access device objects.

In a step 346, the access device receives modifications to the default user object information. For example, the access device can display the default information in a menu. The user or CSR can then select information items from the menu to modify.

5 In an alternative embodiment, the access device prompts the user to enter the new user object information via control device 138 (Figure 2). The access device receives the new or modified user object information and can store it as part of its attributes 231 and data 232 (Figure 7).

10 In a step 352, the access device provides to the server the user object information the access device received for the first user object in step 346. In one embodiment, the access device provides this information in a series of messages to the server. Alternatively, the access device can provide each piece of user object information to the server before prompting the user to enter the next piece of information.

15 In a step 354, the access device receives a ticket number from the server. As previously described, the ticket number indicates the current configuration of the access device. In one embodiment, the server provides a ticket number in response to each piece of user object information received from the access device. This embodiment is useful in embodiments of step 352 in which the
20 access device provides each piece of user object information to the server before prompting the user for the next piece of information.

Figure 16 illustrates one embodiment of adding a user object to a household, according to the present invention. The operational flow of one embodiment starts with a user being logged onto an existing user object. In this
25 exemplary embodiment, the access device is configured to perform the steps of the operational flow.

In a step 360, the access device receives a request to add a new user object. In one embodiment, a user logs onto an existing user object and then enters the request to add the new user object via control device 138 (Figure 2).

In a step 362, the access device is configured to determine whether an administrator attribute was enabled in the existing user object in which the user is logged onto. In one embodiment, the access device can check its own stored user object configurations to determine whether the user object has its administrator attribute enabled. If the existing user object does not have its administrator attribute enabled, the operational flow terminates because in this embodiment only administrators can add a new user object. If the existing user object does have its administrator attribute enabled, the operational flow proceeds to step 344.

As previously described in conjunction with Figure 15, in step 344, the access device then receives default user object information for new user object that is being added. In one embodiment, the access device provisions the new user object with default information, which the access device displays to the user. Alternatively, the access device can be configured to prompt the user to enter the new user object information and skip down to step 352.

In steps 346, 352, and 354 (also described above in conjunction with Figure 15), the access device receives modifications to the default user object information, sends the new user object information to the server and receives one or more ticket numbers associated with the new user object information. In alternative embodiments, the request to add a user mode need not come via an access device. For example, a CSR can make the request and provide the new user mode information using a computer coupled to the server.

Figure 17 illustrates one embodiment of revising a user object, according to the present invention. The operational flow starts with a user being

logged onto an existing user object. In this exemplary embodiment, the access device is configured to perform the steps of the operational flow.

In a step 380, the access device receives a request to revise user object information for an existing logical object. In one embodiment, the user logged
5 onto the existing user object makes the request to revise the existing logical object via control device 138 (Figure 2). In this embodiment, the logical object is a user object. However, in light of the present disclosure, those skilled in the art can implement an operational flow for revising other logical objects without undue experimentation.

10 In a step 382, the access device determines whether an administrator attribute was enabled in the existing user object in which the user is logged onto. In one embodiment, the access device can be configured to check its own stored user object information to determine whether the "logged on" user object has its administrator attribute enabled. The request of step 380 can be to revise the
15 "logged on" user object or another user object in the household. If the "logged on" user object does not have its administrator attribute enabled, the operation flow jumps to a step 386 (described below). In contrast, if the "logged on" user object does have its administrator attribute enabled, the operational flow proceeds to a step 383.

20 In step 383, the access device determines whether the request of step 380 is to revise a protected setting or settings of the exiting user object. For example, as previously described, some attributes can only be changed by an administrator (referred to in this context as a protected setting). If the request is not to revise a protected setting or settings, the operational flow proceeds to step 386
25 (described below). However, if the request is to revise a protected setting or

settings, the operational flow proceeds to a step 384. In an alternative embodiment, step 383 may be performed before step 382.

5 In step 384, the access device can receive the revised setting or settings for the protected setting of the existing user object (*i.e.*, the user object that is being revised). In one embodiment, the user enters the revised setting or settings via an input interface for the access device (e.g., control device 138 in Figure 2).

In step 386, the access device can receive revised non-protected settings for the existing user object. As described in step 384 above, the user can enter the data via an input interface for the access device.

10 In one embodiment, steps 383, 384 and 386 are performed concurrently. The access device may display all of the user object's information, for example, in a menu. The user can select settings to be revised. The access device is configured to determine whether the selected setting is protected. Non-protected settings can be revised by any "logged on" user object. If the setting is protected,
15 the access device is configured to determine whether the "logged on" user object has its administrator attribute enabled before allowing the protected setting to be revised.

Alternatively, the access device can be configured to determine whether the "logged on" user object has its administrator attribute enabled. If
20 enabled, the access device can display a menu with all of the settings (both protected or non-protected). If not enabled, the access device can be configured to display a menu with only non-protected settings. The user could then select and revise any of the displayed settings.

25 In a step 388, the access device provides to the server the revised user object information received in steps 384 and 386. In one embodiment, the access device provides this information in a series of messages to the server.

Alternatively, the access device can provide each piece of user object information to the server before prompting the user to enter the next piece of information. The operational flow then proceeds to step 354, which has been previously described in conjunction with Figure 15.

5 In alternative embodiments, the request to revise a user mode need not come via an access device. For example, a CSR can make the request and provide the revised user mode information using a computer coupled to the server.

10 Figure 18 illustrates one embodiment of using a single password protected logon for accessing multiple password protected services, according to the present invention. In this embodiment, the operational flow starts with a user being logged onto an existing user object. In this exemplary embodiment, the access device is configured to perform the steps of the operational flow.

15 In a step 390, the access device receives a request to access a password protected service (e.g., PPV, VOD, etc.). In one embodiment, the user logged onto the existing user object makes the request for the service via control device 138 (Figure 2).

20 In a step 391, the access device determines whether the user object is authorized to access the service. For example, the user object may have been configured to deny access to the service because the service provides adult or violent content. If the user object is not authorized to access the service, the operational flow proceeds to a step 393.

25 In step 393, the access device provides an indication that the user object is not authorized to access the service, or that the requested access was denied, or other similar message. For example, the access device may display such message via display device 136 (Figure 2).

However, if in step 391 the access device determines that the user object is authorized to access the service, the operational flow proceeds to a step 395. In step 395, the access device determines whether the password corresponding to the requested service and the user object is stored in the access device. This password may be part of the data associated with the access device object (see Table 3 of Appendix A).

If the password is stored in the access device, the operational flow proceeds to a step 396. In step 396, the access device retrieves the password for the requested service from memory 166 (Figure 3).

Conversely, if the password is not stored in the access device, in a step 398 the access device gets the password from the user. For example, the access device may perform a password challenge operation. This feature is useful because some services do not allow the password to be stored on the access device (e.g., access to a “wallet” service).

In a step 399, the access device then sends the password (either retrieved from memory 166 or inputted by the user in response to a password challenge operation) to the service provider. The service provider would then allow access to the service if the password were correct.

The above description of illustrated embodiments of the invention, including what is described in the Abstract, is not intended to be exhaustive or to limit the invention to the precise forms disclosed. While specific embodiments of, and examples for, the invention are described herein for illustrative purposes, various equivalent modifications are possible within the scope of the invention, as those skilled in the relevant art will recognize.

These modifications can be made to the invention in light of the above detailed description. The terms used in the following claims should not be

5

APPENDIX A

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

TABLE 1
USER OBJECTS

User Name	Data that includes an identifier to which all user data and attributes are associated. The user name is unique and is used for logging in from access devices. In some embodiments, the user name can be associated with an email address.
User Password	Data that includes a password used to verify the identity of the user logging in. In one embodiment, the password is not retrievable by a user.
Administrator	An attribute that when enabled allows the user object to have administrative privileges. For example, when logged into a user object with the administrator attribute enabled, the administrator can change or add user object information for other user objects.
User Password Optional	An attribute that when enabled, allows a user to access a television account without a password. This attribute allows a user to view television but not to access other interactive television services.
User Household	Data that includes an identifier used to identify the household to which the user object is associated.
User Email Address	Data that includes an identifier representing the email address of the user object with regard to the interactive television system. In some embodiments, the user email address is the same as the user name.

Email Enabled	An attribute that when enabled allows the user object to access an email account.
Screen Name	Data associated with a user name that is displayed by the access device (for example a set top box). The screen name need only be unique within a household. In a further refinement, if the screen name is not set, the access device can default to displaying the user name.
Deleted	An attribute that when enabled deletes a user object from a household. The user objects data and attributes are not actually deleted, but are not accessible by a user. This attribute allows the interactive television service provider to resurrect the user object as desired.
Revision History	Data used in keeping track of updates to the user object. In one embodiment, the revision history includes entries for each update, each entry having at least a ticket number and a bit vector indicating which configuration perimeter has been updated.
Channel List	Data that includes the channels that are accessible via the user object. For example, a parent can create the channel list for a child with only channels that have no adult or violent content. In another embodiment, the channel list may also include a list of favorite channels, which are a subset of the accessible channels.
Persistent Cookies	Data that includes a list of cookies and associated information maintained on behalf of the user object.
Mail Data	A directory structure for mail folders and message data.

Web Favorites	Data containing a list of favorite web sites or web pages for the user object.
TV Favorites	Data containing a list of favorite television channels, in one embodiment, TV favorites are included in the channel list.
QWERTY Keyboard	An attribute that when enabled displays an onscreen keyboard in the QWERTY format rather than in alphabetical order.
Allow PPV	An attribute that when enabled, allows the user object to purchase pay per view events.
PPV PIN	Data that includes a user object's personal identification number for authorizing a PPV purchase. User object PPV PIN is optional. In an alternative embodiment, the PPV PIN associated with an access device.
Partner Login	Data that includes multiple user names and passwords, each user name and password being associated with a different interactive television service provider partner. This allows a user to log onto a user object with a single password and access services from partners without having to reenter a user name and password for that particular partner.
Login Challenge	A process that occurs when a user begins to log onto a user object from an access device registered with a household. The login challenge displays a list of screen names of all user objects registered in the current household for use when an access device displays a

	login challenge. When a user wishes to log on to a user object, the user selects his or her screen name from the displayed list and enters the password.
External Login Challenge	A process that occurs when a user attempts to access data from an access device that does not belong to the household. The external login challenge can also be used when the access device is not capable of recognizing what household it belongs to. In one embodiment, the external login challenge prompts the user to enter a user name and password.
Anonymous User	Data that includes the attributes and data of an anonymous user object. The anonymous user object is only available when watching full screen television and does not allow access to any interactive television service. The anonymous user object can be accessed by logging out and is the default state on power up. The anonymous user object inherits the common subset of restrictive attributes of all registered user objects in the household.
Logging Out	A process available to any logged in user object. The result of executing the logging out process is the logging in of the anonymous user.
Access Control Lists	Data that includes a list of all privileges available to the user object and a list of registered user objects. An administrator can edit the access control lists to control the privileges available to each registered user.

TABLE 2
HOUSEHOLD

Account ID	Data that includes a unique identifier for an account with an interactive television service provider.
Adding Users	A process that occurs to add a new user object to the household. Additional user objects can be added to the household as long as the number of user objects is less than a specified maximum number. Only an administrator can add a user object to a household.
Removing Users	A process that occurs to remove a user object from a household. The data and attributes associated with the user object are not removed, but the user object is "deleted" (see Table 1). The data and attributes of a deleted user object are not accessible by other users unless an administrator "un-deletes" the user object.
User List	Data that includes a list of registered users within a household. In one embodiment, the user list includes a list of user names.
Current User Count	Data that includes the current number of user objects registered in the household. This number will always be greater than zero and less than or equal to a maximum.
Maximum User Count	Data that includes the maximum number of user objects allowed in a household.
Household Identifier	Data that includes a unique identifier for the household.

TABLE 3
ACCESS DEVICE

Household Identifier	Data that includes the identifier of the household to which the access device belongs.
MAC Address	Data that includes the media access control (MAC) address of the device.
Default User Object	Data that identifies the user object to become active when the access device is first activated or turned on. In one embodiment, the first user object registered in the household is the default user object. If this first user object is password protected, then the anonymous user object becomes the default user object. In one embodiment, an administrator can designate any non-password protected user object in the household to be the default user object.
PPV PIN	Data that contains the personal identification number used for authorizing pay per view services. In one embodiment, the PPV PIN is stored in the access device and is not exposed to users.
Television Control PIN	Data that includes a personal identification number for locking and unlocking channels.

TABLE 4
ACCOUNT

MSO	Data that contains the name of the MSO (Multi-Service Operator) to which the account object is associated.
MSO Account ID	Data that contains the MSO account number to which the account object is associated.
Households List	Data that contains the number of household objects associated with the account object, and the household identifiers of these household objects.
Total Households	Data that contains the number of household objects in the account object. In one embodiment, this information is stored in the Households List.
Total Users	Data that contains the total number of user objects associated with the account object.
Total Access Devices	Data containing the total number of access device objects associated with the account object.